SIROMER MK RANGE

Compact Chassis, High Power.





SIROMER 404MK

The Siromer 40hp MK is available with a fully airconditioned cab.

Complete with shuttle synchro transmission with 8 forward and 8 reverse speeds.

The main shift allows you to shift "on the fly" making operation smooth.

Engineered for power this tractor comes as standard with electric stop start and super steer front mudguards.

MODEL

Horsepower

Maximum 3pl Lift

Weight

Size (Length x Width x Height)

Wheel Base

Turning Circle

Ground Clearance
PTO Speed

Clutch

Clutch

Wheel Drive

Engine

Fuel Tank Capacity

Brakes

Rated Speed

Cultivation Depth Control

Gearbox

Min/Max Speed

Steering

Hydraulic Type

Hitching Mechanism

Hitch Device

Tyres

404MK CAB (K40, K4C)

40HP

1200kg

1580kg (1870kg cab)

3480mm x 1560mm x 2335mm (2465mm cab)

1810mm

3000mm

353mm

2 Speed (540, 1000RPM)

10 Inch Dual Stage Clutch

Salactable 4WD

4 Cylinder, 4 Stroke, Water Cooled Direct Injection Diesel

32 liters

Brakes

2400rpm

Position Control

Shuttle: 8 Forward, 8 Reverse.

1 mph / 18 mph

Hydraulic Power Steering

Dual Double Acting Spool combined single acting spool (20L/min)

Three Point Linkage (CAT I)

Clevis Drawbar

12V 100AH, Combined Instrument Panel, Aux Trailer Connection

Ag: 7.5-16 Front, 12.4-24 Rear